## Film Application

## elcometers inspection equipment

## Elcometer 3580 Casting Knife Film Applicator

The Elcometer 3580 is available in a wide range of film widths and has extended sides to confine the coating during the application and is an ideal gauge for the laboratory.

The film thickness can be adjusted in 10 micron steps from 0 to 6mm by means of two integrated micrometric screws.

Manufactured in anodised aluminium, with a bevelled blade applicator body, the Elcometer 3580 is recommended for manually applying thick, high viscosity fluids, on solid and flat substrates.







STANDARDS: ASTM D 823-E

Technical Specification					C
Part Number	Model	Film Thickness	Film Width <sup>+</sup>		Certificate
		μm	mm	inches	
K0003580M201	Elcometer 3580/1 Casting Knife Film Applicator	0 - 6000	50	2	0
K0003580M202	Elcometer 3580/2 Casting Knife Film Applicator	0 - 6000	75	3	0
K0003580M203	Elcometer 3580/3 Casting Knife Film Applicator	0 - 6000	100	4	0
K0003580M204	Elcometer 3580/4 Casting Knife Film Applicator	0 - 6000	125	5	0
K0003580M005	Elcometer 3580/5 Casting Knife Film Applicator	0 - 6000	150	6	0
K0003580M006	Elcometer 3580/6 Casting Knife Film Applicator	0 - 6000	175	7	0
K0003580M007	Elcometer 3580/7 Casting Knife Film Applicator	0 - 6000	200	8	0

\* Add 15mm (0.6") to the Film Width to calculate the total width of the applicator

## Optional Calibration Certificate available.

© 2016 Elcometer Limited. Elcometer is a registered trademark of Elcometer Limited. All other trademarks acknowledged. Due to our policy of continuous improvement, Elcometer Limited reserves the right to change specifications without notice